

View Online at <https://aerobasegroup.com/nsn/1305-01-476-8159>

**Cartridge Design Type:**

Ball

**Projectile Weight:**

62.0 grains

**Muzzle Velocity:**

Between 3000.0 feet per second and 3100.0 feet per second

**Product Name:**

Federal .223 (5.56mm) ammunition; ball tactical

**Special Features:**

Aload number le223t3; caliber .223remington; case nickel plated brass (copper alloy no 260); bullet 62 grain soft point tactical fusion bonded moly coat; primer federal no 205 nickel plated and basic lead styphnate; primer sealant water resistant lacquer; head stamp fc 224 rem; muzzle energy 1280 foot-pounds; accuracy 5 rd group ave of 2.2 inch at 200 yd from machine rest; chamber pressure 55, 000 psi maximum average; bullet pull min individual 40 lbs

**Supplementary Features:**

4accuracy v-block accuracy barrel, barrel twist 1 in 7 inch, 200 yds equals 2.3 inch; bullet matches the weightof the m855 ball round and is better suited for use in rifles with fast twist rifling rates such as the colt m-4 carbine and the m-16a2

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T007-b