

View Online at <https://aerobasegroup.com/nsn/1375-00-212-4595>

General Description:

Plastic; dim. Data, 1.10 in. Lg, 0.63 in. Od unthreaded end, 0.23 in. Min to 0.24 in. Maximum id unthreaded end, 0.32 in. Min to 0.34 in. Maximum id hole for blasting cap insertion, 0.60 in. Deep hole for blasting cap insertion, 0.065 in. Min to 0.085 in. Maximum w wire slot; thd data, 9/16 in. -12, nc, class 1 fit, 0.25 in. Lg; pkg data, 10, unit qty, cardboard carton, 5, unit qty, fiberboard box, 52, unit qty, wooden box; 1375-m002 dod code; m1a4, model no. Of adapter

Reference Number Differentiating Characteristics:

As mod by dim. Data, 1.10 in. Lg, 0.63 in. Od unthreaded end, 0.23 in. Min to 0.24 in. Maximum id unthreaded end, 0.32 in. Min to 0.34 in. Maximum id hole for blasting cap insertion, 0.60 in. Deep hole for blasting cap insertion, 0.065 in. Min to 0.085 in. Maximum w wire slot, pkg data, 10, unit qty, cardboard carton, 5, unit qty, fiberboard box, 52, unit qty, wooden box, model no. M1a4, model no. Of adapter

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A23900