

View Online at <https://aerobasegroup.com/nsn/1377-00-927-7353>

Casehardening Indicator:

Not casehardened

Overall Length:

Between 0.790 inches and 0.810 inches

Metallic Hardness Rating:

48.0 rockwell c and 50.0 rockwell c

Striking End Diameter:

Between 0.077 inches and 0.078 inches

Striking End Radius:

Between 0.040 inches and 0.045 inches

Firing Pin Type:

Multiple shoulder

Striking End Type:

Spherical

Material:

Steel, qq-s-624, comp 4140h-canceled and steel, qq-s-624, comp 4150h-canceled and steel, qq-s-624, comp 8640h-canceled and steel, qq-s-624, comp 8650h-canceled

Material:

Steel comp 4140h and steel comp 4150h and steel comp 8640h and steel comp 8650h

Material Specification:

Qq-s-624, comp 4140h-canceled federal specification 1st material response and qq-s-624, comp 4150h-canceled federal specification 2nd material response and qq-s-624, comp 8640h-canceled federal specification 3rd material response and qq-s-624, comp 8650h-canceled federal specification 4th material response

Surface Treatment:

Oxide

Surface Treatment:

Black oxide, mil-c-13924, class 1

Fsc Application Data:

Seat, aircraft ejection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T102-d