NSN 1420-00-884-0366

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1420-00-884-0366

Thread Direction:

Thread Direction:
Right-hand
Torque Load Rating:
45.4 inch-pounds
Mounting Type:
Flange
Bolt Circle Diameter:
1.625 inches
Mounting Hole Diameter:
0.281 inches
Mounting Hole Quantity:
4
Thread Size:
7/16 /0.437 in/-20
Shaft Diameter:
0.531 inches
Bolt Hole Quantity:
4
Operating Speed At Rated Capacity In Rpm:
6960.0
Mounting Bolt Circle Diameter:
2.625 inches
Tongue Width:
0.437 inches
Tongue Thickness:
0.198 inches
Bolt Hole Diameter:
0.219 inches
Drive Shaft Type:
Tongue
Housing Material:
Aluminum
Screw Thread Series Designator:
Unf
Shaft Rotation Direction:
Clockwise
Thread Location:
Internal
Shaft Protrusion Length:
0.500 inches
Connection Quantity:

1 and 1

NSN 1420-00-884-0366 Hydraulic Motor - Page 2 of 2



Connection Type:	
Inlet and outlet	
Maximum Working Pressure Rating At Specificationified Tempurature Range:	
3000 psi at minus 65 degrees f to plus 275 degrees f	
Connection Design:	
Threaded and flanged	
Tongue Length:	
0.435 inches	
Displacement Type:	
Constant	
Constant Displacement Per Revolution:	
0.095 cubic inches	
Housing Surface Treatment:	
Anodized	
Fsc Application Data:	
Missile guidance sets	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
Yes - demil/mli	
Fiig:	
T103-f	