## NSN 1430-00-996-0694

Control-indicator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/1430-00-996-0694

Maximum Voltage Rating In Volts:
120.0 ac and 150.0 dc and 250.0 dc
Inclosure Type:
Encased
Terminal Location:
Back
Power Source:
External
Mounting Method:
Rack
Terminal Type And Quantity:
2 threaded stud
Maximumlength:
23.560 inches
Maximumwidth:
13.900 inches
Maximumheight:
9.120 inches
9.120 inches  Phase:
Phase:
Phase: Single
Phase: Single Frequency In Hertz:
Phase: Single Frequency In Hertz: 400.0
Phase: Single Frequency In Hertz: 400.0 Fsc Application Data:
Phase: Single Frequency In Hertz: 400.0 Fsc Application Data: Director station, guided missile, trailer mounted
Phase: Single Frequency In Hertz: 400.0 Fsc Application Data: Director station, guided missile, trailer mounted Shelf Life:
Phase: Single Frequency In Hertz: 400.0 Fsc Application Data: Director station, guided missile, trailer mounted Shelf Life: N/a
Phase: Single Frequency In Hertz: 400.0 Fsc Application Data: Director station, guided missile, trailer mounted Shelf Life: N/a
Phase: Single Frequency In Hertz: 400.0 Fsc Application Data: Director station, guided missile, trailer mounted Shelf Life: N/a Unit Of Measure:
Phase: Single Frequency In Hertz: 400.0 Fsc Application Data: Director station, guided missile, trailer mounted Shelf Life: N/a Unit Of Measure: Demilitarization: