NSN 1560-00-162-2583

Aircraft Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1560-00-162-2583

| Cross Sectional Snape: |
|--------------------------------------------------------------------------|
| Circular recess |
| Hole Diameter: |
| 0.191 inches |
| Bolt Circle Diameter: |
| 3.100 inches |
| Flange Thickness: |
| 0.210 inches |
| Outside Diameter: |
| 3.400 inches |
| Edge Shape: |
| Round, multi holes |
| Bolt Circle Hole Quantity: |
| 8 |
| Second Recess Inside Height: |
| Between 1.675 inches and 1.685 inches |
| Inside Corner Radius: |
| Between 0.215 inches and 0.225 inches |
| Body Thickness: |
| 0.090 inches |
| First Recess Diameter: |
| Between 2.495 inches and 2.505 inches |
| Body Outside Radius: |
| 0.220 inches |
| Securing Device Type: |
| Special |
| Mounting Opening Shape Style: |
| Unthreaded hole |
| Special Features: |
| Contains center opening 0.630 in. Diameter with four holes 0.070 in. Dia |
| Material: |
| Aluminum alloy |
| Material Specification: |
| Qq-a-591 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, ty2 military specification single treatment response |
| Supplementary Features: |
| Aluminum alloy 360 |
| Shelf Life: |
| N/a |

NSN 1560-00-162-2583

Aircraft Access Cover - Page 2 of 2



| | | eas | |
|--|--|-----|--|
| | | | |

--

Demilitarization:

Yes - demil/mli

Fiig:

A531h0

Mil-std (military Standard):

Mil-a-8625 spec.