NSN 1560-01-424-2476

Aircraft Structural Component Support - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/1560-01-424-2476 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.425 inches |
| Fastener Length: |
| 2.113 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| 0.125 inches |
| Width Between Flats: |
| Between 0.429 inches and 0.439 inches |
| Grip Diameter: |
| Between 0.2485 inches and 0.2495 inches |
| Shank Unthreaded Hole Diameter: |
| 0.076 inches first hole |
| End Application: |
| Aircraft e-3 |
| Thread Diameter: |
| 0.2500 inches |
| Grip Length: |
| 1.688 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 1.935 inches first hole |
| Special Features: |
| Bolt |
| Color: |
| Green threads |
| Material: |
| Iron alloy 660 |
| Surface Treatment: |
| Chromate and cadmium |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |

N/a

NSN 1560-01-424-2476

Aircraft Structural Component Support - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

Yes - demil/mli

Fiig:

A11800