NSN 1560-01-474-4412

Aircraft Fairing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/1560-01-474-4412

Overall Length: 24.654 inches End Application: Sh-2 (a) seasprite helicopter Side For Which Designed: Left side Product Name: Nose gear box and cross shaft fairing - fairing assembly, left engine Aircraft Station Number: W1127.00 and bl34.5 Aircraft Mission Design Series: Sh-2 (a) Special Features: Two temperature sensors embedded within fiberglass structure of forward fairing for temp. Monitoring; socket head cap screws with lockwire; components normally shipped looseunless specifically defined by purchase order; fairing construction thickness Except in areas of temp. Sensors, electrical lead wire, flanges, hardware attachment or as specified; assembly consists of fair assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life: N/a	
End Application: Sh-2 (a) seasprite helicopter Side For Which Designed: Left side Product Name: Nose gear box and cross shaft fairing - fairing assembly, left engine Aircraft Station Number: Wl127.00 and bl34.5 Aircraft Mission Design Series: Sh-2 (a) Special Features: Two temperature sensors embedded within fiberglass structure of forward fairing for temp. Monitoring; socket head cap screws with lockwire; components normally shipped looseunless specifically defined by purchase order; fairing construction thickness Except in areas of temp. Sensors, electrical lead wire, flanges, hardware attachment or as specified; assembly consists of fair assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:	
Sh-2 (a) seasprite helicopter Side For Which Designed: Left side Product Name: Nose gear box and cross shaft fairing - fairing assembly, left engine Aircraft Station Number: Wl127.00 and bl34.5 Aircraft Mission Design Series: Sh-2 (a) Special Features: Two temperature sensors embedded within fiberglass structure of forward fairing for temp. Monitoring; socket head cap screws with lockwire; components normally shipped looseunless specifically defined by purchase order; fairing construction thickness Except in areas of temp. Sensors, electrical lead wire, flanges, hardware attachment or as specified; assembly consists of fair assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:	
Side For Which Designed: Left side Product Name: Nose gear box and cross shaft fairing - fairing assembly, left engine Aircraft Station Number: Wl127.00 and bl34.5 Aircraft Mission Design Series: Sh-2 (a) Special Features: Two temperature sensors embedded within fiberglass structure of forward fairing for temp. Monitoring; socket head cap screws with lockwire; components normally shipped looseunless specifically defined by purchase order; fairing construction thickness Except in areas of temp. Sensors, electrical lead wire, flanges, hardware attachment or as specified; assembly consists of fair assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:	
Left side Product Name: Nose gear box and cross shaft fairing - fairing assembly, left engine Aircraft Station Number: W1127.00 and bl34.5 Aircraft Mission Design Series: Sh-2 (a) Special Features: Two temperature sensors embedded within fiberglass structure of forward fairing for temp. Monitoring; socket head cap screws with lockwire; components normally shipped looseunless specifically defined by purchase order; fairing construction thickness Except in areas of temp. Sensors, electrical lead wire, flanges, hardware attachment or as specified; assembly consists of fair assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:	
Product Name: Nose gear box and cross shaft fairing - fairing assembly, left engine Aircraft Station Number: W1127.00 and bl34.5 Aircraft Mission Design Series: Sh-2 (a) Special Features: Two temperature sensors embedded within fiberglass structure of forward fairing for temp. Monitoring; socket head cap screws with lockwire; components normally shipped looseunless specifically defined by purchase order; fairing construction thickness Except in areas of temp. Sensors, electrical lead wire, flanges, hardware attachment or as specified; assembly consists of fair assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:	
Nose gear box and cross shaft fairing - fairing assembly, left engine Aircraft Station Number: W1127.00 and bl34.5 Aircraft Mission Design Series: Sh-2 (a) Special Features: Two temperature sensors embedded within fiberglass structure of forward fairing for temp. Monitoring; socket head cap screws with lockwire; components normally shipped looseunless specifically defined by purchase order; fairing construction thickness Except in areas of temp. Sensors, electrical lead wire, flanges, hardware attachment or as specified; assembly consists of fair assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:	
Aircraft Station Number: W1127.00 and bl34.5 Aircraft Mission Design Series: Sh-2 (a) Special Features: Two temperature sensors embedded within fiberglass structure of forward fairing for temp. Monitoring; socket head cap screws with lockwire; components normally shipped looseunless specifically defined by purchase order; fairing construction thickness Except in areas of temp. Sensors, electrical lead wire, flanges, hardware attachment or as specified; assembly consists of fair assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:	
Aircraft Mission Design Series: Sh-2 (a) Special Features: Two temperature sensors embedded within fiberglass structure of forward fairing for temp. Monitoring; socket head cap screws with lockwire; components normally shipped looseunless specifically defined by purchase order; fairing construction thickness Except in areas of temp. Sensors, electrical lead wire, flanges, hardware attachment or as specified; assembly consists of fair assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:	
Aircraft Mission Design Series: Sh-2 (a) Special Features: Two temperature sensors embedded within fiberglass structure of forward fairing for temp. Monitoring; socket head cap screws with lockwire; components normally shipped looseunless specifically defined by purchase order; fairing construction thickness Except in areas of temp. Sensors, electrical lead wire, flanges, hardware attachment or as specified; assembly consists of fair assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:	
Sh-2 (a) Special Features: Two temperature sensors embedded within fiberglass structure of forward fairing for temp. Monitoring; socket head cap screws with lockwire; components normally shipped looseunless specifically defined by purchase order; fairing construction thickness Except in areas of temp. Sensors, electrical lead wire, flanges, hardware attachment or as specified; assembly consists of fair assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:	
Special Features: Two temperature sensors embedded within fiberglass structure of forward fairing for temp. Monitoring; socket head cap screws with lockwire; components normally shipped looseunless specifically defined by purchase order; fairing construction thickness Except in areas of temp. Sensors, electrical lead wire, flanges, hardware attachment or as specified; assembly consists of fair assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:	
Two temperature sensors embedded within fiberglass structure of forward fairing for temp. Monitoring; socket head cap screws with lockwire; components normally shipped looseunless specifically defined by purchase order; fairing construction thickness Except in areas of temp. Sensors, electrical lead wire, flanges, hardware attachment or as specified; assembly consists of fair assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:	
with lockwire; components normally shipped looseunless specifically defined by purchase order; fairing construction thickness Except in areas of temp. Sensors, electrical lead wire, flanges, hardware attachment or as specified; assembly consists of fair assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:	
Except in areas of temp. Sensors, electrical lead wire, flanges, hardware attachment or as specified; assembly consists of fair assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:	ire secured
assembly, forward, left hand p/n k870302-103; fairing assembly, aft upper, left hand p/n k870302-105; and fairing assembly, left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:).100 in.
left hand p/n k870302-107; station location sta 120.75; opposite of p/n k870302-102 Shelf Life:	ng
Shelf Life:	aft lower,
N/a	
11/4	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A11500	