

View Online at <https://aerobasegroup.com/nsn/1610-00-858-8495>

General Description:

Cres, mil-s-5059 comp 302 or qq-s-763 comp 304, tube, support and washers, tube dim., 0.385 in. Min, 0.387 in. Maximum id, 0.495 in. Min, 0.497 in. Maxin. Od, 1.440 in. Nom straight lg for filter section w/one inlet slot 0.900 in. Lg, 0.120 in. W located 0.180 in. From right end, 2nd section 1.140 in. Lg bent at 153 degrees angle w/integral mtg support located 0.440 in. From left end, 0.211 in. Min, 0.217 in. Maximum diameter mtg hole in. Support, filter dim., body style cylindrical, 0.855 in. Nom id, 1.310 in. Nom lg, 1st end 0.835 in. Min, 0.845 in. Maximum od, 0.497 in. Min, 0.499 in. Maximum id, 0.080 in. Nom thick, 2nd end, 0.835 in. Min, 0.845 in. Maximum od0.383 in. Min, 0.385 in. Maximum id, filtering material, cres, aisi 304 el c or aisi 347 wire mesh 0.009 in. Wire dia, 50x50 mesh size, entire perimeter bonded

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No