

View Online at <https://aerobasegroup.com/nsn/1610-00-858-8528>

General Description:

Steel, ams 5616, rockwell hardness rating c scale 40 to 50, dim., 1.914 in. Min, 1.930 in. Maximum lg, 0.628 in. Min, 0.630 in. Maximum od, 1.591 in. Nom od lg, 0.450 in. Min, 0.460 in. Maximum id by 1.591 in. Lg, 1.113 in. Min, 1.115 in. Maxflange od, 0.260 in. Min, 0.270 in. Maximum flange w, 0.2324 in. Min, 0.2484 in. Maxflange id by 0.217 in. Lg, flange left end closed, 0.195 in. W flange groove by 0.947 in. Nom diameter 0.140 in. From left end, eight equally spaced holes 0.120 in. Diameter drilled 0.350 in. Deep at 22 degrees angle from flange body cornerto flange id, two holes 0.219 in. Diameter 180 degrees apart drilled through od 0.375 in. From right end, four equally spaced slots 0.170 in. W by 0.079 in. Deep by 1.460 in. Lg on od 0.131 in. From right end, made by 0.593 in. Nom diameter cutter magnetic particle inspected, magnafluxed, mil-i-6868

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No