

View Online at <https://aerobasegroup.com/nsn/1610-00-991-3265>

General Description:

Aluminum alloy qq-a-282 temper t6rockwell hardness rating b scale 88 min, dim., 2.590 in. Min, 2.593 in. Maximum o/a lg, 0.2910 in. Min, 0.2914 in. Maximum left end id by 1.370 in. Min, 1.376 in.Max id lg, 0.536 in. Min, 0.538 in. Maximum right end id by 1.217 in. Min, 1.220 in. Maximum id lg, 0.653 in. Min, 0.659 in. Maximum right end counterbore dia, 0.148 in. Min, 0.154 in. Maximum counterbore lg, left end od chamfered 0.050 in. Lg by 45 deg, four grooved flanges on od for packing, preformed with 0.098 in. Wide grooves, 00.493 in. Nom 1st left end flange od by 0.280 in. W, 0.555 in. Nom2nd left flange od by 0.198 in. W 0.730 in. From left end, 0.618 in. Nom 3rd left flange od by 0.300 in. W 1.703 in. From left end, 0.747 in. Nom right end flange od by 0.372 in. W, four holes 0.188 in. Diameter equally spaced drilled through od 0.600 in. From left end, three cuts 0.185 in. W equally spaced made by 1.000 in. Diameter cutter on od 0.970 in. From left end, two holes 0.188 in. Diameter equally spaceddrilled through od 1.880 in. From left end, ma

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No