## NSN 1615-00-051-3646

Crosshead Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/1615-00-051-3646

## **General Description:**

Aluminum alloy qq-a-268 comp 2024-t4, surface treatment anodized bps fw4001, dim., 6.000 in. Nom o/a lg, 1.250 in. Nom center ht by 1.300 in. Square center, 0.960 in. Nom left and right arm ht, 1.062 in. Min, 1.064 in. Maximum left and right arm w, 0.750 in. Min, 0.752 in. Maximum left and right arm end slot w, 1.120 in. Nom left and right arm end slot depth, two holes in-line on left ano right slot ends 0.3750 in. Diameter 2.500 in. From center, no. 204-010-794-1 bushing installed in each hole, 0.900 in. Id drilled in bottom center by 1.130 in. Deep and counterbored 1.0236 in. Min, 1.0241 in. Maximum diameter by 0.605 in. Deep, one lub fitting nas516-1 installed in top center through 0.1235 in. Diameter hole, one mounting hole drilled on top 1.063 in. Each side of center 0.259 in. Dia, item used on tail rotor

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

Yes - demil/mli