

View Online at <https://aerobasegroup.com/nsn/1615-00-121-6566>

**General Description:**

Aluminum alloy ww-t-700/3 type 1 temper 3, anodized bps fw4352 shaft, aluminum alloy qq-a-367 comp 2014-t6 anodized right flanged adapter, steel ams6371 comp 4130 type 1 cond n sliding adapter, shaft dim., 143.170 in. Nom o/a lg, 1.000 in. Nom shaft dia, flanged adapter dim., 2.937 in. Nom flange lg, 0.650 in. Flange w, 0.300 in. Nom flange thk, 2.450 in. Nom adapter lg, 2.3438 in. C to c distance between flange mounting holes, adapter bonded to shaft right ensliding adapter dim., 3.725 in. Nom o/alg, 2.225 in. Nom plain end lg, 0.8700 left end id tapered to 0.65x0 in. Id at 2.000 in. From left end, od involutespline data, 15 teeth 1.475 in. Lg, 16/32 diametral pitch, 30.0 degrees pressure angle, 0.9375 in. Pitch dia, 0.8475 in. Min, 0.8588 in. Maximum minor dia, 0.9994 in. Min, 0.9999 in. Maximum major dia, plug no. 206-040-343-1 and two o-rings no. Ms29561-018 inserted into sline id and unit bonded to shaft left end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli