## NSN 1615-00-625-0039

Pylon Assembly Mast Nut Lock - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/1615-00-625-0039

## **General Description:**

Steel, mil-s-6758, comp 4130, cadmium plated qq-p-416 class 1, type 1, dim., 1.000 in. Nom lg, 0.355 in. Nom w, 0.625in. Nom thk, one hole 0.260 in. Min, 0.267 in. Maximum diameter located 0.420 in. From bottom and 0.461 in. From right side, left side chamfered at 45.0 degrees angle by 0.350 in. Lg, right side chamferedat 45.0 degrees angle by 0.250 in. Lg, three tines located on bottom lg 0.148 in.Thk, 0.240 in. From front and back, leftand right tines 0.120 in. W by 0.045 in. Lg, center tine 0.110 in. W by 0.110 in. Lg w/both sides tapered at 60.0 degrees angle, max surface finish 125 microinches aa o/a

angle by 0.550 in. Eg, fight side chamileredat 45.0 degrees angle by 0.250 in. Eg, times times located on bottom ig 0.140 in. This, 0.240 in.
From front and back, leftand right tines 0.120 in. W by 0.045 in. Lg, center tine 0.110 in. W by 0.110 in. Lg w/both sides tapered at 60.0
degrees angle, max surface finish 125 microinches aa o/a
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli