

View Online at <https://aerobasegroup.com/nsn/1615-00-775-7766>

**General Description:**

Steel, ams6260 comp 9310, cadmium-plated qq-p-416 bearing end, carburized shank, dim., 7.883 in. Nom o/a lg, 4.319 in. Min, 4.325 in. Maximum shank lg, 1.1253 in. Min, 1.1258 in. Maximum shank right endod by 1.250 in. Lg, 1.6255 in. Min, 1.6258 in. Maximum shank left end od by 1.250 in. Lg, 2.187 in. Flange od by 0.125 in. Thk located 6.228 in. From right end, two flats on flange od w/1.990 in. Distance across flats, 0.966-32 ns class 3 threads on right end od by 0.406 in. Lg, 0.625 in. Right end id by 6.687 in. Lg counterbored to 0.6875 in. Diameter by 0.312 in. Lg, eye bolt end 1.249 in. Thk, bolt end rounded by 1.093 in. Radius, eye drilled w/1.6241 in. Diameter hole w/one s1510-23389 inner race and one gr-18-rss mcgill bearing installed in hole, 2.062 in. Distance from right flange face to bearing center, one ms15002-1 lubricator installed on bolt end od, item used on main rotor

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli