

View Online at <https://aerobasegroup.com/nsn/1615-00-998-0448>

**General Description:**

Steel, mil-s-5000 or mil-s-5626 or mil-s-6049 or mil-s-6098 or mil-s-8503, cadmium, qq-p-416, type 1, class 3 o/a, rockwell hardness rating c36 min, c40 max, dim., 0.562-18 unf 3a thread size and class, right-hand thread, 0.815 in. Min, 0.865 in. Maximum thread lg, 3.075 in. Min, 3.105 in. Maximum fastener lg, 0.281 in. Nom head height, 0.865 in. Min, 0.877 in. Maximum width between flats, 2.240 in. Min, 2.260 in. Maximum grip lg, 0.5605 in. Min, 0.5615 in. Maximum grip dia, one hole drilled through threads 0.141 in. Nom dia, 0.218 in. Nom from bolt end, one steel washer 0.968 in. Nom od, 0.573 in. Nom d, 0.078 in. Nom thk, part no. Ms20002c9, one steel spacer, sleeve 0.982 in. Nom lg, 0.7491 in. Nom od, 0.5625 in. Nom id, part no. 204-040-118-1, bolt used on liftlink, transmission

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli