NSN 1650-00-011-9022

Servocylinder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-00-011-9022

Body Material:

Aluminum alloy, qq-a-225/6, alloy 2024, t4

First End Outside Diameter:

Between 0.496 inches and 0.498 inches

Tempurature Rating:

160.0 degrees fahrenheit

Overall Height:

Between 3.210 inches and 3.270 inches

Overall Width:

2.000 inches

Bore Diameter:

1.260 inches

Seat Angle In Deg:

45.0 all ports

First End External Thread Length:

1.250 inches

Compressed Length:

Between 11.760 inches and 11.900 inches

Extended Length:

Between 12.660 inches and 12.800 inches

Pressure Rating:

1500.0 pounds per square inch

Integral Valve Operation Method:

Hydraulic

Design Characteristics:

Single acting single cylinder

First Piston Rod End Style:

External threaded

First Piston Rod End Thread Series Designator:

Unf

First Piston Rod End Thread Diameter:

0.4375 inches

First Piston Rod End Thready Qty Per Inch (tpi):

20

First Piston Rod End Thread Class:

За

First Piston Rod End Thread Direction:

Right-hand

Mounting Type And Location:

Boss cylinder head end

Port Location And Quantity:

1 center section

NSN 1650-00-011-9022 Servocylinder - Page 2 of 2

Fiig: A34200



Port Style:
Gasket seal single port
Port Thread Series Designator:
Unf single port
Port Thread Diameter:
0.438 inches single port
Port Thready Qty Per Inch (tpi):
20 single port
Port Thread Class:
3b all ports
Test Data Document:
97499-570-076-002 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli