NSN 1650-00-014-1765



Hydraulic Motor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/1650-00-014-1765 **Thread Direction:** Right-hand **Torque Load Rating:** 1800.0 inch-pounds **Spline Minor Diameter:** Between 0.346 inches and 0.349 inches **Spline Major Diameter:** Between 0.406 inches and 0.409 inches **Mounting Type:** Flange **Spline Quantity:** 12 **Mounting Hole Diameter:** 0.422 inches **Mounting Hole Quantity: Thread Size:** 9/16-18 **Operating Speed At Rated Capacity In Rpm:** 94.0 or 114.0 Pitch Diameter: 0.3750 inches **Drive Shaft Type:** Splined, involute internal **Housing Material:** Aluminum alloy **Screw Thread Series Designator:** Unf **Shaft Rotation Direction:** Clockwise **Thread Location:** Internal Spline Pitch: 32/64 **Connection Quantity: Connection Type:** Outlet **Maximum Working Pressure Rating At Specificationified Tempurature Range:** 3000 at minus 65 degrees f to plus 225 degrees f **Connection Design:**

Connection Design

Threaded

NSN 1650-00-014-1765 Hydraulic Motor - Page 2 of 2



Spline Pressure Angle In Deg:
30.0
Spline Length:
1.125 inches
Mounting Government Standard:
And 10260
Displacement Type:
Constant
Connection Government Specification/std:
And 10050-4
Mounting Bolt Hole Spacing:
1.870 by1.870 in. C to c
Housing Surface Treatment:
Anodized
Fsc Application Data:
Hydraulic system aircraft
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
Yes - demil/mli
Fiig:
Г103-f