NSN 1650-00-014-2038

Aluminum alloy, qq-a-268, comp 2024, t4-canceled

Servocylinder - Page 1 of 2

Second End Outside Diameter:

Body Material:

0.593 inches

Pin

Mounting Provision:



View Online at https://aerobasegroup.com/nsn/1650-00-014-2038

Tempurature Rating:
180.0 degrees celsius
Mounting Facility Length:
0.500 inches
Overall Height:
Between 2.980 inches and 3.030 inches
Overall Width:
2.600 inches
Bore Diameter:
1.066 inches
Body Outside Diameter:
Between 1.390 inches and 1.410 inches
Seat Angle In Deg:
120.0
First End Hole Diameter:
0.3437 inches
Integral Valve Operation Method:
Hydraulic
Design Characteristics:
Double acting single cylinder
First Piston Rod End Style:
Fork type (clevis)
First End Largest Inside Diameter:
Between 0.249 inches and 0.250 inches
First End Fork Width:
0.700 inches
First End Fork Depth:
1.600 inches
First End Fork Span Width:
0.751 inches
Mounting Type And Location:
Trunnion center section
Mounting Facility Diameter:
0.4991 inches
Port Location And Quantity:
2 piston rod end

NSN 1650-00-014-2038

Servocylinder - Page 2 of 2



Port Style:
Gasket seal
Port Thread Series Designator:
Unjf
Port Thread Diameter:
0.437 inches
Port Thready Qty Per Inch (tpi):
20
Port Thread Class:
3b
Shelf Life:
N/a
Unit Of Measure:
--Demilitarization:
Yes - demil/mli

Fiig: A34200