## NSN 1650-00-079-4630

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-00-079-4630

Torque Load Rating:
220.0 inch-pounds
Spline Minor Diameter:
0.550 inches
Spline Major Diameter:
Between 0.645 inches and 0.650 inches
Mounting Type:
Flange
Spline Quantity:
12
Mounting Hole Diameter:
Between 0.339 inches and 0.354 inches
Mounting Hole Quantity:
4
Operating Speed At Rated Capacity In Rpm:
2400.0
Pitch Diameter:
0.600 inches
Drive Shaft Type:
Splined, involute external
Shaft Rotation Direction:
Clockwise and counterclockwise
Shaft Protrusion Length:
1.060 inches
Spline Pitch:
20/40
Connection Quantity:
2 and 1 and 1
Connection Type:
Outlet
Connection Design:
Threaded and threaded
Spline Pressure Angle In Deg:
30.0
Spline Length:
0.812 inches
Drive Shaft Government Standard:
And 10261
Mounting Government Standard:
And 10261
Displacement Type: Variable
variable

## NSN 1650-00-079-4630

Hydraulic Motor - Page 2 of 2



## **Constant Displacement Per Revolution:**

0.660 cubic inches

**Connection Government Specification/std:** 

Ms33649-4, ms33642-8 and ms33642-8

**Mounting Bolt Hole Spacing:** 

3.536 in. By 3.536 in.

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

Fiig:

T103-f