## NSN 1650-00-105-6258



Servocylinder - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/1650-00-105-6258 **Body Material:** Aluminum alloy, qq-a-367, comp 7075, t6 **Mounting Provision:** Unthreaded mounting holes **Overall Height:** 6.535 inches **Overall Width:** 3.380 inches **Bore Diameter:** 0.830 inches **Longest Horizontal Distance Between Mounting Centers:** 3.100 inches **Longest Vertical Distance Between Mounting Centers:** 2.750 inches First End Hole Diameter: Unable to decode **Mounting Provision Arrangement Style:** Four hole rectangular **Pressure Rating:** 1500.0 pounds per square inch **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Double acting twin cylinder First Piston Rod End Style: Fork type (clevis) Piston Rod End Similarity: Identical First End Fork Width: Unable to decode First End Fork Depth: 1.028 inches First End Fork Span Width: Unable to decode

Mounting Type And Location:
Lug center section
Mounting Facility Diameter:
0.252 inches
Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 1650-00-105-6258

Servocylinder - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A34200