## NSN 1650-00-133-6270

Servocylinder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-00-133-6270

Body Material:
Steel, mil-s-5000, comp 4340, cond a
First End Outside Diameter:
Unable to decode
Inside Diameter:
0.172 inches single port
Mounting Provision:
Unthreaded mounting holes
Outside Diameter:
0.774 inches 4th port
Tempurature Rating:
Not rated
Overall Height:
4.780 inches
Overall Width:
13.285 inches
Bore Diameter:
1.6865 inches
Seat Angle In Deg:
120.0
First End Hole Diameter:
Unable to decode
First End Thickness At Mounting Holes:
Unable to decode
Compressed Length:
27.250 inches
Extended Length:
39.750 inches
Mounting Provision Arrangement Style:
Two hole
Pressure Rating:
200.0 pounds per square inch
Integral Valve Operation Method:
Hydraulic
Design Characteristics:
Single acting twin cylinder
First Piston Rod End Style:
Bearing type
Mounting Type And Location:
Flange center section
Mounting Facility Diameter:
0.4995 inches

## **NSN 1650-00-133-6270** Servocylinder - Page 2 of 2



Center To Center Distance Between Mounting Provisions:
7.5015 inches
Port Location And Quantity:
2 center section
Port Style:
Gasket seal
Port Thread Series Designator:
Unjf
Port Thread Diameter:
0.5625 inches all ports
Port Thready Qty Per Inch (tpi):
20 single port
Port Thread Class:
3b
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fila:

A34200