NSN 1650-00-143-8276

Servocylinder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-00-143-8276

Body Material:

Aluminum alloy, qq-a-268, comp 2024, t4-canceled

Second End Outside Diameter:

0.593 inches

Mounting Provision:

Pin

Tempurature Rating:

180.0 degrees celsius

Mounting Facility Length:

0.500 inches

Overall Height:

Between 2.980 inches and 3.030 inches

Overall Width:

2.600 inches

Bore Diameter:

1.066 inches

Body Outside Diameter:

Between 1.390 inches and 1.410 inches

Seat Angle In Deg:

120.0

First End Hole Diameter:

0.3437 inches

Pressure Rating:

Not rated

Integral Valve Operation Method:

Hydraulic

Design Characteristics:

Double acting single cylinder

First Piston Rod End Style:

Fork type (clevis)

First End Largest Inside Diameter:

Between 0.249 inches and 0.250 inches

First End Fork Width:

0.700 inches

First End Fork Depth:

1.600 inches

First End Fork Span Width:

0.751 inches

Mounting Type And Location:

Trunnion center section

Mounting Facility Diameter:

0.4991 inches

NSN 1650-00-143-8276 Servocylinder - Page 2 of 2



Port Location And Quantity:
2 piston rod end
Port Style:
Gasket seal
Port Thread Series Designator:
Unjf
Port Thread Diameter:
0.437 inches
Port Thready Qty Per Inch (tpi):
20
Port Thread Class:
3b
Reference Number Differentiating Characteristics:
As differentiated by part no. 204-076-053-5, fsmc 97499
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A34200