NSN 1650-00-168-5151

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-00-168-5151

Thread Direction:
Right-hand and right-hand
Spline Minor Diameter:
0.433 inches
Spline Major Diameter:
0.517 inches
Mounting Type:
Flange
Spline Quantity:
11
Mounting Hole Diameter:
0.281 inches
Mounting Hole Quantity:
4
Thread Size:
0.438-20 and 0.500-20
Operating Speed At Rated Capacity In Rpm:
10000.0
Pitch Diameter:
0.458 inches
Drive Shaft Type:
Splined, involute external
Housing Material:
Steel, corrosion resisting
Screw Thread Series Designator:
Unf and unf
Shaft Rotation Direction:
Clockwise
Thread Location:
Internal and internal
Shaft Protrusion Length:
Between 0.656 inches and 0.666 inches
Spline Pitch:
24/48
Connection Quantity:
2 and 1 and 1
Connection Type:
Drain and inlet and outlet
Maximum Working Pressure Rating At Specificationified Tempurature Range:
3000 psi at minus 65 degrees to plus 275 degrees f
Connection Design:
Threaded and threaded

NSN 1650-00-168-5151 Hydraulic Motor - Page 2 of 2



Spline Pressure Angle In Deg:
30.0
Spline Length:
0.500 inches
Mounting Government Standard:
And 10260
Displacement Type:
Constant
Mounting Bolt Hole Spacing:
1.876 in. By 1.876 in.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
T103-f