## NSN 1650-00-493-5041

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-00-493-5041 **Body Material:** Aluminum alloy **Mounting Provision:** Unthreaded mounting holes **Tempurature Rating:** -65.0 degrees fahrenheit and 275.0 degrees fahrenheit **Bore Diameter:** Between 1.116 inches and 1.118 inches Seat Angle In Deg: 60.0 all ports **Compressed Length:** Between 5.010 inches and 5.250 inches **Extended Length:** Between 6.580 inches and 6.820 inches **Pressure Rating:** 3000.0 pounds per square inch **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: Bearing type all working ends **Mounting Type And Location:** Lug cylinder head end **Port Location And Quantity:** 1 cylinder head end and 1 piston rod end Port Style: Gasket seal all ports **Port Thread Series Designator:** Unf all ports **Port Thread Diameter:** 0.438 inches all ports Port Thready Qty Per Inch (tpi): 20 all ports **Port Thread Class:** 3b all ports Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** Yes - demil/mli

## NSN 1650-00-493-5041

Linear Actuating Cylinder Assembly - Page 2 of 2



Fiig:

A34200