## NSN 1650-00-508-1308



Hydraulic Motor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/1650-00-508-1308 **Thread Direction:** Right-hand **Torque Load Rating:** 22.0 inch-pounds **Mounting Type:** Flange **Spline Quantity:** 10 **Mounting Hole Diameter:** Between 0.276 inches and 0.291 inches **Mounting Hole Quantity: Thread Size:** 0.438-20 **Operating Speed At Rated Capacity In Rpm:** 14070.0 **Pitch Diameter:** 0.312 inches **Drive Shaft Type:** Splined, involute internal **Screw Thread Series Designator:** Unjf **Shaft Rotation Direction:** Counterclockwise **Thread Location:** Internal Spline Pitch: 32/64 **Connection Quantity: Connection Type:** Inlet and outlet **Maximum Working Pressure Rating At Specificationified Tempurature Range:** 

3000psi at minu 65 degrees f to plus 275 degrees f **Connection Design:** Threaded **Spline Pressure Angle In Deg:** 30.0

Spline Length:

0.660 inches

**Connection Government Specification/std:** 

Ms33649-4

## NSN 1650-00-508-1308

Hydraulic Motor - Page 2 of 2



Mounting	Bolt	Hole	Spa	cing
----------	------	------	-----	------

0.938 in. By 0.938 in.

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

T103-f