NSN 1650-00-510-9974

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-00-510-9974 **Body Material:** Steel First End Outside Diameter: 1.400 inches **Mounting Provision:** Pin **Tempurature Rating:** Not rated **Bore Diameter:** 1.752 inches **Body Outside Diameter:** Between 2.026 inches and 2.028 inches Seat Angle In Deg: 120.0 First End Hole Diameter: 0.500 inches First End Thickness At Mounting Holes: 0.625 inches **Compressed Length:** 12.914 inches **Extended Length:** 13.347 inches **Pressure Rating:** 3000.0 pounds per square inch **Features Provided:** Filler plug **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: Bearing type **Mounting Type And Location:** Trunnion piston rod end **Port Location And Quantity:** 1 cylinder head end Port Style: Gasket seal **Port Thread Series Designator:** Unf **Port Thread Diameter:** 0.565 inches Port Thready Qty Per Inch (tpi):

18

NSN 1650-00-510-9974

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Thread Class:
3b
Shelf Life:
Shelf Life: N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A34200