NSN 1650-00-523-7724

Fluid Filter - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/1650-00-523-7724 |
|---|
| Mounting Type: |
| Inlet connection line and outlet connection line |
| Body Outside Diameter: |
| 1.250 inches |
| Body Height: |
| Between 4.970 inches and 5.030 inches |
| Filtration Rating In Microns: |
| 25.00 |
| Drop Pressure: |
| 1500.0 pounds per square inch |
| Differential Pressure: |
| 7500.0 pounds per square inch |
| Design Type: |
| Reusable |
| Tempurature Rating: |
| Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit |
| Filtering Element Quantity: |
| 1 |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Filtering Media Design: |
| Sintered single filtering media response |
| First Intake Connection Type: |
| Threaded internal pipe bottom |
| First Discharge Connection Relationship To Intake Connection: |
| Not identical |
| First Discharge Connection Type: |
| Threaded external pipe top |
| First Intake Thread Series Designator: |
| Unf |
| First Discharge Thread Series Designator: |
| Unf |
| First Intake Thread Size: |
| 0.750 inches |
| First Discharge Thread Size: |
| 0.750 inches |
| First Intake Thread Class: |
| 3b |
| First Discharge Thread Class: |
| 3a |

Right-hand

First Intake Thread Direction:

NSN 1650-00-523-7724

Fluid Filter - Page 2 of 2



| First Discharge Thread Direction: |
|--------------------------------------|
| Right-hand |
| Filtering System For Which Designed: |
| Full flow |
| Material: |
| Copper alloy filtering medium |
| Media For Which Designed: |
| Air |
| Style Designator: |
| High pressure threaded body |
| Fsc Application Data: |
| Hydraulic system aircraft |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: A24000