

View Online at <https://aerobasegroup.com/nsn/1650-00-540-0156>

Thread Direction:

Right-hand and right-hand and right-hand

Torque Load Rating:

725.0 inch-pounds

Spline Minor Diameter:

0.867 inches

Spline Major Diameter:

0.727 inches

Mounting Type:

Flange

Spline Quantity:

16

Mounting Hole Diameter:

0.344 inches

Mounting Hole Quantity:

4

Thread Size:

0.563-18 and 0.875-14 and 0.875-14

Operating Speed At Rated Capacity In Rpm:

2820.0

Pitch Diameter:

0.800 inches

Drive Shaft Type:

Splined, involute external

Housing Material:

Aluminum alloy

Screw Thread Series Designator:

Unf and unf and unf

Shaft Rotation Direction:

Clockwise and counterclockwise

Thread Location:

Internal and internal and internal

Shaft Protrusion Length:

1.000 inches

Spline Pitch:

20/30

Connection Quantity:

2 and 1 and 1

Connection Type:

Outlet

Maximum Working Pressure Rating At Specificationified Temperature Range:

3000 psi at minus 65 degrees f to plus 275 degrees f

Connection Design:

Threaded and threaded and threaded

Spline Pressure Angle In Deg:

30.0

Spline Length:

0.625 inches

Drive Shaft Government Standard:

And10262

Mounting Government Standard:

And10621

Displacement Type:

Constant

Constant Displacement Per Revolution:

1.519 cubic inches

Connection Government Specification/std:

And10050-6, and10050-10 and and10050-10

Mounting Bolt Hole Spacing:

3.536 in. By 3.536 in. C to c

Housing Surface Treatment:

Anodized

Fsc Application Data:

Aircraft hydraulic system b52

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T103-f