# NSN 1650-00-574-7520

Servocylinder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-00-574-7520

Aluminum alloy, comp 2024, temper t4

#### First End Outside Diameter:

Between 0.3112 inches and 0.3117 inches

### **Mounting Provision:**

Threaded mounting studs

#### **Tempurature Rating:**

160.0 degrees fahrenheit

#### **Mounting Facility Length:**

1.837 inches

#### **Overall Height:**

1.812 inches

#### **Overall Width:**

2.370 inches

#### **Bore Diameter:**

Between 1.250 inches and 1.260 inches

#### **Body Outside Diameter:**

1.300 inches

# Seat Angle In Deg:

120.0

# **Mounting Facility Thread Direction:**

Right-hand

#### **Compressed Length:**

Between 7.780 inches and 8.060 inches

#### **Extended Length:**

Between 14.670 inches and 14.850 inches

#### **Mounting Provision Arrangement Style:**

Two hole

#### **Pressure Rating:**

300.0 pounds per square inch

# **Mounting Facility Thread Series Designator:**

Unf

#### **Mounting Facility Thread Diameter:**

0.190 inches

#### Mounting Facility Thready Qty Per Inch (tpi):

10

# **Integral Valve Operation Method:**

Hydraulic

# **Design Characteristics:**

Single acting single cylinder

#### **Mounting Type And Location:**

Trunnion piston rod end

# **NSN 1650-00-574-7520** Servocylinder - Page 2 of 2



Mounting Facility Thread Length
0.313 inches
Port Location And Quantity:
2 cylinder head end
Port Style:
Gasket seal
Port Thread Series Designator:
Jnjf
Port Thread Diameter:
0.4375 inches
Port Thready Qty Per Inch (tpi):
20
Port Thread Class:
За
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:

A34200