## NSN 1650-00-580-6029

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-00-580-6029
Mounting Type:
Inlet connection line and outlet connection line
Body Length:
3.219 inches
Body Outside Diameter:
1.375 inches
Filtration Rating In Microns:
10.00
Drop Pressure:
35.0 pounds per square inch
Differential Pressure:
4000.0 pounds per square inch
Design Type:
Nonreusable
Tempurature Rating:
Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit
Filtering Element Quantity:
1
Maximum Operating Pressure:
3000.0 pounds per square inch
Filtering Media Design:
Convoluted single filtering media response
First Intake Connection Type:
Threaded external tube end
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Unf
First Intake Thread Size:
0.453 inches
First Intake Thread Class:
3a
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Material:
Stainless steel filtering medium
Media For Which Designed:
Fuel/oil, hydrocarbon

Style Designator: Inline (hydraulic)

## NSN 1650-00-580-6029

Fluid Filter - Page 2 of 2



Fsc Application Data	Fsc Appl	ication	Data
----------------------	----------	---------	------

Tubing instl, hydraulic system, vertical stabilzer, acft

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A24000