NSN 1650-00-684-6510

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-00-684-6510

view Online at https://aerobasegroup.com/nsn/1650-00-684-6510
Mounting Type:
Inlet connection side or outlet connection side
Design Type:
Reusable
Features Provided:
By-pass valve
Filtering Element Quantity:
2
Maximum Operating Pressure:
5000.0 pounds per square inch
Filtering Media Design:
Encased 1st filtering media response
First Intake Connection Type:
Threaded internal tube side
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Un
First Discharge Thread Series Designator:
Un
First Intake Thread Size:
1.938 inches
First Discharge Thread Size:
1.938 inches
First Intake Thready Qty Per Inch (tpi):
16
First Discharge Thready Qty Per Inch (tpi):
16
First Intake Thread Class:
2a
First Discharge Thread Class:
2a
First Intake Thread Direction:
Right-hand
First Discharge Thread Direction:
Right-hand
Filtering System For Which Designed:
By-pass flow
Material:
Steel sediment bowl
Fsc Application Data:

Test stand, specialized maintenance equipment, aircraft

NSN 1650-00-684-6510

Fluid Filter - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A24000