NSN 1650-00-690-9725



Hydraulic Motor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/1650-00-690-9725 **Thread Direction:** Right-hand **Torque Load Rating:** 65.0 inch-pounds **Spline Minor Diameter:** 0.3563 inches **Spline Major Diameter:** 0.4188 inches **Mounting Type:** Flange **Spline Quantity:** 12 **Mounting Hole Diameter:** 0.281 inches **Mounting Hole Quantity: Thread Size:** 7/16-20 **Operating Speed At Rated Capacity In Rpm:** 10000.0 Pitch Diameter: 0.2651 inches **Drive Shaft Type:** Splined, involute internal **Housing Material:** Aluminum alloy **Screw Thread Series Designator:** Unf **Shaft Rotation Direction:** Clockwise **Thread Location:** Internal Spline Pitch: 32/64 **Connection Quantity:**

Connection Type:

Drain

Maximum Working Pressure Rating At Specificationified Tempurature Range:

3000 psi at minus 65 degrees f to plus 275 degrees f

Connection Design:

Threaded

NSN 1650-00-690-9725 Hydraulic Motor - Page 2 of 2



Spline Pressure Angle In Deg:
30.0
Spline Length:
0.688 inches
Mounting Government Standard:
And10260
Displacement Type:
Constant
Constant Displacement Per Revolution:
0.188 cubic inches
Connection Government Specification/std:
And 10050-8
Mounting Bolt Hole Spacing:
1.876 in. By 1.876 in. C to c
Housing Surface Treatment:
Anodized
Fsc Application Data:
Hydraulic system aircraft
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T103-f