NSN 1650-00-738-6841

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-00-738-6841
Body Material:
Aluminum alloy, qq-a-225/6, alloy 2024, t4
Mounting Provision:
Unthreaded mounting holes
Tempurature Rating:
-65.0 degrees fahrenheit and 160.0 degrees fahrenheit
Overall Height:
2.500 inches
Overall Width:
2.500 inches
Bore Diameter:
1.876 inches
Body Outside Diameter:
2.020 inches
Overall Diameter:
2.500 inches
Seat Angle In Deg:
60.0 all ports
Compressed Length:
10.850 inches
Extended Length:
16.550 inches
Pressure Rating:
1500.0 pounds per square inch
Integral Valve Operation Method:
Hydraulic
Design Characteristics:
Double acting single cylinder
First Piston Rod End Style:

Bearing type all working ends

Mounting Type And Location:

Lug cylinder head end

Mounting Facility Diameter:

0.375 inches

Port Location And Quantity:

1 cylinder head end and 1 piston rod end

Port Style:

Gasket seal all ports

Port Thread Series Designator:

Unf all ports

Port Thread Diameter:

0.438 inches all ports

NSN 1650-00-738-6841

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Thready Qty Per Inch (tpi):
20 all ports
Port Thread Class:
3b all ports
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A34200