

View Online at <https://aerobasegroup.com/nsn/1650-00-756-1046>

Thread Direction:

Right-hand and right-hand and right-hand

Torque Load Rating:

175.2 inch-pounds

Spline Minor Diameter:

0.550 inches

Spline Major Diameter:

0.664 inches

Mounting Type:

Flange

Spline Quantity:

12

Mounting Hole Diameter:

0.344 inches

Mounting Hole Quantity:

4

Thread Size:

0.750-16 and 0.750-16 and 0.438-20

Operating Speed At Rated Capacity In Rpm:

3850.0

Mounting Bolt Circle Diameter:

5.000 inches

Pitch Diameter:

0.600 inches

Drive Shaft Type:

Splined, involute internal

Housing Material:

Aluminum alloy

Screw Thread Series Designator:

Unf and unf and unf

Shaft Rotation Direction:

Clockwise and counterclockwise

Thread Location:

Internal and internal and internal

Spline Pitch:

20/40

Connection Quantity:

1 and 1 and 1

Connection Type:

Inlet and outlet and drain

Maximum Working Pressure Rating At Specificationified Temperature Range:

3000 psi at minus 65 degrees f to plus 275 degrees f

Connection Design:

Threaded and threaded and threaded

Spline Pressure Angle In Deg:

30.0

Spline Length:

0.906 inches

Mounting Government Standard:

And10261

Displacement Type:

Constant

Constant Displacement Per Revolution:

0.367 cubic inches

Connection Government Specification/std:

Ms33649-8 and ms33649-8 and ms33649-4

Housing Surface Treatment:

Anodized

Fsc Application Data:

Hydraulic system aircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T103-f