

View Online at <https://aerobasegroup.com/nsn/1650-00-756-1046>

**Thread Direction:**

Right-hand and right-hand and right-hand

**Torque Load Rating:**

175.2 inch-pounds

**Spline Minor Diameter:**

0.550 inches

**Spline Major Diameter:**

0.664 inches

**Mounting Type:**

Flange

**Spline Quantity:**

12

**Mounting Hole Diameter:**

0.344 inches

**Mounting Hole Quantity:**

4

**Thread Size:**

0.750-16 and 0.750-16 and 0.438-20

**Operating Speed At Rated Capacity In Rpm:**

3850.0

**Mounting Bolt Circle Diameter:**

5.000 inches

**Pitch Diameter:**

0.600 inches

**Drive Shaft Type:**

Splined, involute internal

**Housing Material:**

Aluminum alloy

**Screw Thread Series Designator:**

Unf and unf and unf

**Shaft Rotation Direction:**

Clockwise and counterclockwise

**Thread Location:**

Internal and internal and internal

**Spline Pitch:**

20/40

**Connection Quantity:**

1 and 1 and 1

**Connection Type:**

Inlet and outlet and drain

**Maximum Working Pressure Rating At Specificationified Temperature Range:**

3000 psi at minus 65 degrees f to plus 275 degrees f

**Connection Design:**

Threaded and threaded and threaded

**Spline Pressure Angle In Deg:**

30.0

**Spline Length:**

0.906 inches

**Mounting Government Standard:**

And10261

**Displacement Type:**

Constant

**Constant Displacement Per Revolution:**

0.367 cubic inches

**Connection Government Specification/std:**

Ms33649-8 and ms33649-8 and ms33649-4

**Housing Surface Treatment:**

Anodized

**Fsc Application Data:**

Hydraulic system aircraft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T103-f