

View Online at <https://aerobasegroup.com/nsn/1650-00-834-1430>

Thread Direction:

Right-hand and right-hand and right-hand

Torque Load Rating:

23.0 inch-pounds

Spline Minor Diameter:

0.458 inches

Spline Major Diameter:

0.460 inches

Mounting Type:

Flange

Spline Quantity:

11

Mounting Hole Diameter:

Between 0.280 inches and 0.286 inches

Mounting Hole Quantity:

4

Thread Size:

0.562-18 and 0.562-18 and 0.438-20

Operating Speed At Rated Capacity In Rpm:

6330.0

Drive Shaft Type:

Splined, straight external

Screw Thread Series Designator:

Unf and unf and unf

Shaft Rotation Direction:

Clockwise and counterclockwise

Thread Location:

Internal and internal and internal

Connection Quantity:

1 and 1 and 1

Connection Type:

Inlet and outlet and drain

Maximum Working Pressure Rating At Specificationified Temperature Range:

3000 psi at minus 65 degrees to plus 160 degrees f

Connection Design:

Threaded and threaded and threaded

Spline Length:

0.500 inches

Mounting Government Standard:

And 10260

Displacement Type:

Constant

Connection Government Specification/std:

Ms33649-6 and ms33649-6 and ms33649-4

Mounting Bolt Hole Spacing:

1.876 in. C to c

Fsc Application Data:

Winch, cargo, acft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T103-f