NSN 1650-00-887-1903

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-00-887-1903

Threa	ad Direction:
Right	-hand
Torqu	ue Load Rating:
45.4 i	inch-pounds
Splin	e Minor Diameter:
0.408	Binches
Splin	e Major Diameter:
0.500) inches
Mour	nting Type:
Flang	le
Splin	e Quantity:
11	
Mour	nting Hole Diameter:
0.281	inches
Mour	nting Hole Quantity:
4	
Threa	ad Size:
0.562	-18
Opera	ating Speed At Rated Capacity In Rpm:
6060.	.000
Pitch	Diameter:
0.458	33 inches
Drive	e Shaft Type:
Spline	ed, involute external
Hous	ing Material:
Alumi	inum alloy
Screv	w Thread Series Designator:
Unf	
Shaft	Rotation Direction:
Clock	wise and counterclockwise
Threa	ad Location:
Intern	nal
Splin	e Pitch:
24/48	;
Conn	nection Quantity:
1	
Conn	nection Type:
Outle	t
Maxiı	mum Working Pressure Rating At Specificationified Tempurature Range:
3000	psi minus 65 degrees f to plus 160 degrees f
~	nection Design:

Threaded and threaded and threaded

NSN 1650-00-887-1903

Hydraulic Motor - Page 2 of 2

Aero	Base
	Group

Spline Pressure Angle In Deg: 30.000 Spline Length: 0.500 inches Mounting Government Standard: And 10260 **Displacement Type:** Constant **Constant Displacement Per Revolution:** 0.095 cubic inches **Connection Government Specification/std:** And 10050-6 Mounting Bolt Hole Spacing: 1.876 in. By 1.876 in. C to c Housing Surface Treatment: Anodized Shelf Life: N/a Unit Of Measure: ---Demilitarization: Yes - demil/mli Fiig: T103-f