

View Online at <https://aerobasegroup.com/nsn/1650-00-887-1903>

Thread Direction:

Right-hand

Torque Load Rating:

45.4 inch-pounds

Spline Minor Diameter:

0.408 inches

Spline Major Diameter:

0.500 inches

Mounting Type:

Flange

Spline Quantity:

11

Mounting Hole Diameter:

0.281 inches

Mounting Hole Quantity:

4

Thread Size:

0.562-18

Operating Speed At Rated Capacity In Rpm:

6060.000

Pitch Diameter:

0.4583 inches

Drive Shaft Type:

Splined, involute external

Housing Material:

Aluminum alloy

Screw Thread Series Designator:

Unf

Shaft Rotation Direction:

Clockwise and counterclockwise

Thread Location:

Internal

Spline Pitch:

24/48

Connection Quantity:

1

Connection Type:

Outlet

Maximum Working Pressure Rating At Specificationified Temperature Range:

3000 psi minus 65 degrees f to plus 160 degrees f

Connection Design:

Threaded and threaded and threaded

Spline Pressure Angle In Deg:

30.000

Spline Length:

0.500 inches

Mounting Government Standard:

And 10260

Displacement Type:

Constant

Constant Displacement Per Revolution:

0.095 cubic inches

Connection Government Specification/std:

And 10050-6

Mounting Bolt Hole Spacing:

1.876 in. By 1.876 in. C to c

Housing Surface Treatment:

Anodized

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T103-f