NSN 1650-00-912-4122

Servocylinder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-00-912-4122

Body Material:

Aluminum alloy, qq-a-268, comp 2024, t4-canceled

Second End Outside Diameter:

0.593 inches

Mounting Provision:

Pin

Tempurature Rating:

180.0 degrees celsius

Mounting Facility Length:

0.500 inches

Overall Height:

Between 2.980 inches and 3.030 inches

Overall Width:

2.600 inches

Bore Diameter:

1.066 inches

Body Outside Diameter:

Between 1.390 inches and 1.410 inches

Seat Angle In Deg:

120.0

First End Hole Diameter:

0.3437 inches

Pressure Rating:

Not rated

Integral Valve Operation Method:

Hydraulic

Design Characteristics:

Double acting single cylinder

First Piston Rod End Style:

Fork type (clevis)

Piston Rod End Similarity:

Not identical

First End Fork Width:

0.700 inches

First End Fork Depth:

1.600 inches

First End Fork Span Width:

0.751 inches

Mounting Type And Location:

Trunnion center section

Mounting Facility Diameter:

0.4991 inches

NSN 1650-00-912-4122

Servocylinder - Page 2 of 2



Port Location And Quantity:

2 piston rod end

Port Style:

Gasket seal

Port Thread Series Designator:

Unjf

Port Thready Qty Per Inch (tpi):

20

Port Thread Class:

3b

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A34200