NSN 1650-00-944-8169

Aluminum alloy, qq-a-268, comp 2024, t4-canceled

Servocylinder - Page 1 of 2

Second End Outside Diameter:

Body Material:

0.593 inches

Pin

Mounting Provision:

Tempurature Rating:



View Online at https://aerobasegroup.com/nsn/1650-00-944-8169

180.0 degrees celsius
Mounting Facility Length:
0.500 inches
Overall Height:
Between 2.980 inches and 3.030 inches
Overall Width:
2.600 inches
Bore Diameter:
1.066 inches
Body Outside Diameter:
Between 1.390 inches and 1.410 inches
Seat Angle In Deg:
120.0
First End Hole Diameter:
0.3437 inches
Pressure Rating:
Not rated
Integral Valve Operation Method:
Hydraulic
Design Characteristics:
Double acting single cylinder
First Piston Rod End Style:
Fork type (clevis)
Piston Rod End Similarity:
Not identical
First End Fork Width:
0.700 inches
First End Fork Depth:
1.600 inches
First End Fork Span Width:
0.751 inches
Mounting Type And Location:
Trunnion center section
Mounting Facility Diameter:
0.4991 inches

NSN 1650-00-944-8169 Servocylinder - Page 2 of 2



Port Location And Quantity:
2 piston rod end
Port Style:
Gasket seal
Port Thread Series Designator:
Unjf
Port Thready Qty Per Inch (tpi):
20
Port Thread Class:
3b
Reference Number Differentiating Characteristics:
As differentiated by part no. 204-076-053-11, fsmc 97499
As differentiated by part no. 204-076-053-11, fsmc 97499 Shelf Life:
Shelf Life:
Shelf Life: N/a
Shelf Life: N/a
Shelf Life: N/a Unit Of Measure:
Shelf Life: N/a Unit Of Measure: Demilitarization: