NSN 1650-00-996-3908

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-00-996-3908

view Crimie at https://aerobasegroup.com/risi
Body Material:
Aluminum alloy, qq-a-200/11, alloy 7075, t6
First End Outside Diameter:
Err-070
Mounting Provision:
Pin
Tempurature Rating:
Not rated
Mounting Facility Length:
2.537 inches
Bore Diameter:
1.995 inches
Body Outside Diameter:
Between 2.300 inches and 2.340 inches
Overall Diameter:
Between 3.860 inches and 4.060 inches
First End Hole Diameter:
0.5000 inches
First End Thickness At Mounting Holes:
0.688 centimeters
Compressed Length:
Between 29.992 inches and 30.146 inches
Extended Length:
Between 46.242 inches and 46.396 inches
Pressure Rating:
3000.0 pounds per square inch
Integral Valve Operation Method:
Hydraulic
Design Characteristics:
Single acting single cylinder
First Piston Rod End Style:
Bearing type
Mounting Type And Location:
Tongue cylinder head end
Mounting Facility Diameter:
0.6250 inches
Port Location And Quantity:
3 cylinder head end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 1650-00-996-3908

Linear Actuating Cylinder Assembly - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A34200