NSN 1650-01-170-3999

Hydraulic Motor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/1650-01-170-3999

| Mounting Type: |
|--|
| Pad |
| Mounting Hole Diameter: |
| Between 0.323 inches and 0.326 inches |
| Mounting Hole Quantity: |
| 4 |
| Drive Shaft Type: |
| Splined, straight internal |
| Shaft Rotation Direction: |
| Clockwise and counterclockwise |
| Spline Pitch: |
| 20/40 |
| Connection Quantity: |
| 2 |
| Connection Type: |
| Inlet |
| Maximum Working Pressure Rating At Specificationified Tempurature Range: |
| 3000psi at minus 40 degrees f to plus 275 degrees f |
| Spline Pressure Angle In Deg: |
| 30.0 |
| Mounting Government Standard: |
| And10261 |
| Displacement Type: |
| Constant |
| Mounting Bolt Hole Spacing: |
| 3.536 in. By 3.536 in. |
| Reference Number Differentiating Characteristics: |
| As differentiated by the source control dwg no. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| T103-f |
| |