## NSN 1650-01-189-3349

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-01-189-3349

| view Offiline at https://acrobasegroup.com/nsi//1000-01-109-0049 |
|--|
| Mounting Type:   |
| Inlet connection head side and outlet connection head side       |
| Body Length:   |
| 2.750 inches   |
| Body Width:  |
| 1.812 inches   |
| Body Height:   |
| 9.060 inches   |
| Filtration Rating In Microns:                                    |
| 5.0 absolute   |
| Design Type:   |
| Reusable   |
| Tempurature Rating:  |
| 270.0 degrees fahrenheit   |
| Filtering Element Quantity:                                      |
| 1  |
| Maximum Operating Pressure:                                      |
| 3000.0 pounds per square inch                                    |
| First Intake Connection Type:                                    |
| Threaded internal tube head side                                 |
| First Discharge Connection Relationship To Intake Connection:    |
| Identical to first intake connection                             |
| Distance From Bottom Of Body To Center Of Inlet:                 |
| 5.485 inches   |
| First Intake Thread Series Designator:                           |
| Unjf   |
| First Intake Thread Size:  |
| 0.563 inches   |
| First Intake Thread Class:                                       |
| 3b   |
| First Intake Thread Direction:                                   |
| Right-hand   |
| Filtering System For Which Designed:                             |
| By-pass flow   |
| Material:  |
| Steel body   |
| Media For Which Designed:  |
| Fuel/oil, hydrocarbon  |
| Style Designator:  |
| Tee type (hydraulic)   |

N/a

Shelf Life:

## NSN 1650-01-189-3349

Fluid Filter - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

Yes - demil/mli

Fiig:

A24000

Mil-std (military Standard):

Mil-f-8815 spec.