NSN 1650-01-281-5383

Hydraulic Servovalve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/1650-01-281-5383

End	Ann	lica	ıtin	n
LIIU	TPP	1100	ILIO	•••

B-1b aircraft

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Maximum Operating Pressure:

4000.0 pounds per square inch

Special Features:

Consist of: manifold assembly control 1, cap, control valve 1, lap assembly, control valve 1, spring, control valve 2, guide, spring 2, lap assemb, down command 1, retainer, control valve 1, cover 2, cap, lockvalve 1, spring, lockvalve 1, lap assembly, lockvalve 1, sleeve inner 1, solenoid 3, adapter 2, switch, pressure 4, plug 1, packing 29, backup 36, seal assembly 15, screw 27, washer 10, terminal 1, wire ar, solder ar, sealant ar, stop 1, restictor assembly 1, spacer 1, cap, relief valve1, check valve 1, relief valve assembly 1; proof pressure 6000.0, burst pressure 10000.0 psig; service fliud per mil-h-5606

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A508u0