## NSN 1650-01-289-3702

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1650-01-289-3702

Mounting Type:
Unthreaded hole head
Mounting Hole Diameter:
0.266 inches
Mounting Hole Quantity:
2
Body Outside Diameter:
2.000 inches
Body Height:
6.000 inches
Filtration Rating In Microns:
15.0 absolute
Drop Pressure:
20.0 pounds per square inch
Differential Pressure:
4500.0 pounds per square inch
Distance Between Mounting Hole Centers:
1.500 inches
End Application:
F-4 aircraft
Design Type:
Reusable
Tempurature Rating:
Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit
Features Provided:
Differential pressure indicator
Filtering Element Quantity:
1
Maximum Operating Pressure:
3000.0 pounds per square inch
Filtering Media Design:
Porous single filtering media response
First Intake Connection Type:
Threaded internal tube head side
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Unjf
First Intake Thread Size:
0.563 inches
First Intake Thread Class:

3b

## NSN 1650-01-289-3702

Fluid Filter - Page 2 of 2



First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
Disposable element; aluminum surfaces anodized
Material:
Rubber buna n seal
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
High pressure threaded body
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

**Fiig:** A24000