

View Online at <https://aerobasegroup.com/nsn/1650-01-397-7038>

Mounting Type:

Threaded hole head

Mounting Hole Quantity:

4

Body Outside Diameter:

2.720 inches

Body Height:

6.660 inches

Filtration Rating In Microns:

3.0 absolute

Drop Pressure:

14.0 pounds per square inch

Differential Pressure:

9000.0 pounds per square inch

Distance Between Mounting Hole Centers:

Between 1.181 inches and 1.772 inches

End Application:

Helicopter, ah-64a

Mounting Facility Thread Direction:

Right-hand

Design Type:

Reusable

Temperature Rating:

Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit

Features Provided:

Differential pressure indicator

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unf

Maximum Operating Pressure:

6000.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal tube head side

Mounting Facility Thread Size:

0.190 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Unf

First Intake Thread Size:

0.750 inches

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

W/o by-pass valve

Material:

Stainless steel sediment bowl

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Supplementary Features:

Next higher assembly is 4320-01-345-0478 power driven hydraulic pumping unit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000