

View Online at <https://aerobasegroup.com/nsn/1650-01-527-9312>

Torque Load Rating:

175.2 inch-pounds

Mounting Type:

Face

Spline Quantity:

12

Mounting Hole Quantity:

4

Operating Speed At Rated Capacity In Rpm:

3860.0

Mounting Bolt Circle Diameter:

Between 0.343 inches and 0.350 inches

End Application:

E/i an/slq-48 simsl, (for sima use only); and vehicle, submersible mine locator, (mns); next assemblies: 5266000, 6097300 and 6916045

Pitch Diameter:

0.600 inches

Housing Material:

Aluminum

Shaft Rotation Direction:

Counterclockwise

Spline Pitch:

20/40

Connection Quantity:

3

Connection Type:

Outlet

Maximum Working Pressure Rating At Specificationified Temperature Range:

3000psi at plus 28.4 degrees f to plus 89.6 degrees f

Connection Design:

Threaded

Spline Pressure Angle In Deg:

30.0

Displacement Type:

Constant

Constant Displacement Per Revolution:

0.367 cubic inches

Connection Government Specification/std:

33649-4 and 33649-8

Mounting Bolt Hole Spacing:

3.536 in. By 3.536 in.

Special Features:

Dimensions: length 5.200 maximum by 4.250 square

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T103-f