

View Online at https://aerobasegroup.com/nsn/1660-01-005-6318

| 0  | verall Depth:                 |
|----|-------------------------------|
| 4. | 250 inches                    |
| 0  | verall Height:                |
| 3. | 000 inches                    |
| 0  | verall Width:                 |
| 5. | 750 inches                    |
| Μ  | ounting Method:               |
| Pa | anel                          |
| In | stallation Design:            |
| N  | onportable                    |
| Pr | ressure Gage:                 |
| In | cluded                        |
| FI | ow Indicator:                 |
| In | cluded                        |
| 0  | n-off Switch:                 |
| In | cluded                        |
| Li | ghted Panel:                  |
| In | cluded                        |
| Er | mergency Oxygen Control Type: |
| S١ | vitch                         |
| M  | arking Finish:                |
| W  | hite                          |
| Er | rr Default:                   |
| Er | r default                     |
| In | let Connection Size:          |
| 1/ | 8 in. Npt                     |
| Vo | oltage In Volts:              |
| 28 | 3.000                         |
| Sı | urface Treatment:             |
| D  | ull black                     |
| SI | helf Life:                    |
| N/ | 'a                            |
| U  | nit Of Measure:               |
|    |                               |
| De | emilitarization:              |
| Ye | es - demil/mli                |
| Fi | ig:                           |
| Τ1 | 164-h                         |