

View Online at <https://aerobasegroup.com/nsn/1660-01-592-7327>

**Special Features:**

Passenger, paratrooper and medical oxygen supply. Removable ballistic protection portable liquid oxygen system. Specifications: medium oxygen flow rate 200 slpm maximum pax outlet pressure 75 +/- psig, 4.1 to 6.2 bar, medical outlet pressure 50 +/- 5 psig, 3.1 to 3.8 bar, weight 300lbs max, 136 kg, battery life 100 operational hours ballistic protection nij-std-0108, level iii dimensions 25.7 w x 25.6 l x 25.1 w, 65.3cm x 65 cm x 63.8 cm, operating environment temperature -40 to 131 degrees f, -14 to 55 degrees c, altitude sea level to 25,000 ft, 7620 m, humidity type 0 to 100%, shock 20 g non-operating environment temperature -40 to 131 degrees f, -40 to 55 degrees c, humidity type 0 to 100% product interfaces fill valve mil-prf-25961, cru-50, grounding receptacle ms90298-2 medical outlet m7891lf-3 pax outlet 4-pin q

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A23900

**Mil-std (military Standard):**

Mil-prf-25961 spec.